

## Key Features

- Featuring NXP's KW41Z
- ARM® Cortex®-M0+, 128 kB SRAM and 512 kB Flash
- Single and concurrent operation of Thread® and Bluetooth® 4.2 LE
- Flexible usage with Host mode and Stand-alone mode
- SMT Size: 15.6mm x 8.7mm x 1.9mm
- Voltage range: 1.8V to 4.2V
- Temperature range: -40°C to 85 °C
- 6.1mA Tx (0 dBm) / 6.8mA Rx (1Mbps)
  @3.6V

# PAN4620 Bluetooth®4.2 LE and IEEE® 802.15.4 Module

## Panasonic INDUSTRY

### IoT Dual Mode Module


The PAN4620 is Panasonic's Internet of Things dual mode module comprising NXP's Kinetis KW41Z SoC - a 2.4 GHz 802.15.4 and Bluetooth® Low Energy wireless radio microcontroller based on an ARM® Cortex-M0+ core. Using the PAN4620 with low power consumption in combination with NXP's certified Thread® stack, Bluetooth® Low Energy stack or a combination of both for concurrent operation allows to meet IoT application requirements without the need for a gateway.



#### **Industrial IoT**

- Smart Energy / Occupancy Sensor
- Access Control Security Systems
- Industrial Mesh Networks





Powered Patient Beds

• Wireless Insulin Pump



For further Information, please contact wireless.connectivity@eu.panasonic.com