

GP Batteries

Material Safety Data Sheet for GP Lithium battery (Lithium Metal Battery)

Document Number: MCRA003W

Revision:19

Page 1 of 5

IDENTITY (As Used on Label and List)
Lithium Metal batteries

Note : Blank spaces are not permitted if any item is not applicable or no information is available, the space must be marked to indicate that.

Section 1- Identification

Manufacturer's Name GPI International Ltd.	Emergency Telephone Number
Address (Number, Street, City State, and ZIP Code) 8/F GP Building, 30 Kwai Wing Road, Kwai Chung, N.T. H.K.	Telephone Number for information 852-2484-3333
	Date of prepared and revision May 19, 2012
	Signature of Prepare (optional)

Section 2 – Hazards Identification

Classification:

N.A.

Section 3 – Composition/Information On Ingredients

Hazardous Components:

Description:	CAS Number	Approximate % of total weight
Lead	7439-92-1	<0.004 Wt%
Mercury	7439-97-6	<0.0005 Wt%
Cadmium	7440-43-9	<0.002 Wt%
Lithium	7439-93-2	1.2-6.7 Wt%

Section 4 – First Aid Measures

First Aid Procedures

If electrolyte leakage occurs and makes contact with skin, wash with plenty of water immediately.

If electrolyte comes into contact with eyes, wash with copious amounts of water for fifteen (15) minutes, and contact a physician.

If electrolyte vapors are inhaled, provide fresh air and seek medical attention if respiratory irritation develops. Ventilate the contaminated area.

Section 5 – Fire-Fighting Measures

Flash Point (Method Used) N.A.	Ignition Temp. N.A.	Flammable Limits N.A.	LEL N.A.	UEL N.A.
-----------------------------------	------------------------	--------------------------	-------------	-------------

Extinguishing Media

Carbon Dioxide, Dry Chemical or Foam extinguishers

Special Fire Fighting Procedures

N.A.

Unusual Fire and Explosion Hazards

Do not dispose of battery in fire - may explode.

Do not short-circuit battery - may cause burns.

GP Batteries

Material Safety Data Sheet for GP Lithium battery (Lithium Metal Battery)

Document Number: MCRA003W

Revision:19

Page 2 of 5

Section 6 – Accidental Release Measures

Steps to Be Taken in Case Material is Released or Spilled

Batteries that are leakage should be handled with rubber gloves.

Avoid direct contact with electrolyte.

Wear protective clothing and a positive pressure Self-Contained Breathing Apparatus (SCBA).

Section 7 – Handling and Storage

Safe handling and storage advice

Batteries should be handled and stored carefully to avoid short circuits.

Do not store in disorderly fashion, or allow metal objects to be mixed with stored batteries.

Never disassemble a battery.

Do not breathe cell vapors or touch internal material with bare hands.

The cells and batteries shall not be stored in high temperature ,the maximum temperature allowed is 60°C for a short period during the shipment , Otherwise the cells maybe leakage and can result in shortened service life..

Section 8– Exposure Controls / Person Protection

Occupational Exposure Limits:	LTEP	STEP		
	N.A.	N.A.		
Respiratory Protection (Specify Type)	N.A.			
Ventilation	Local Exhausts	N.A.	Special	N.A.
	Mechanical (General)	N.A.	Other	N.A.
Protective Gloves	N.A.	Eye Protection	N.A.	
Other Protective Clothing or Equipment	N.A.			
Work / Hygienic Practices	N.A.			

Section 9 - Physical / Chemical Properties

Boiling Point	N.A.	Specific Gravity (H ₂ O=1)	N.A.
Vapor Pressure (mm Hg)	N.A.	Melting Point	N.A.
Vapor Density (AIR=1)	N.A.	Evaporation Rate (Butyl Acetate)	N.A.
Solubility in Water	N.A.		
Appearance and Odor	Cylindrical Shape, odorless		

GP Batteries

Material Safety Data Sheet for GP Lithium battery (Lithium Metal Battery)

Document Number: MCRA003W

Revision:19

Page 3 of 5

Section 10 – Stability and Reactivity

Stability	Unstable		Conditions to Avoid
	Stable	X	

Incompatibility (Materials to Avoid)

Hazardous Decomposition or Byproducts

Hazardous Polymerization	May Occur		Conditions to Avoid
	Will Not Occur	X	

Section 11 – Toxicological Information

Route(s) of Entry Inhalation? N.A. Skin? N.A. Ingestion? N.A.

Health Hazard (Acute and Chronic) / Toxicological information

In case of electrolyte leakage, skin will be itchy when contaminated with electrolyte.

In contact with electrolyte can cause severe irritation and chemical burns.

Inhalation of electrolyte vapors may cause irritation of the upper respiratory tract and lungs.

Section 12 – Ecological Information

N.A.

Section 13 – Disposal Considerations

Dispose of batteries according to government regulations.

GP Batteries

Material Safety Data Sheet for GP Lithium battery (Lithium Metal Battery)

Document Number: MCRA003W

Revision:19

Page 4 of 5

Section 14 – Transportation Information

All GP lithium Photo batteries (Lithium Metal Battery) comply to the necessary requirements under the UN Manual of Tests and Criteria as referenced in the following transportation regulations:

1. UN Recommendations on the Transport of Dangerous Goods Model Regulations
2. U.S. Department of Transportation hazardous materials regulations (HMR),
3. International Civil Aviation Organization (ICAO) Technical Instructions,
4. International Air Transport Association (IATA) Dangerous Goods Regulations, Partially Regulated DG section II of PI 968 and
5. International Maritime Dangerous Goods (IMDG) Code. Special Provision 188, Special Provision 230 & Special Provision 903

GP lithium Photo Batteries are exempted from these regulations since they meet all UN Testing requirements and not exceed 1g lithium equivalent for single cell and 2g lithium equivalent for battery. (UN3090.) Non-dangerous Goods.

All GP lithium Photo battery (Lithium Metal Battery) packaging comply with Partially regulated DG. section II of PI 968.

Cells & batteries should be packaged in accordance with these transportation regulations. It is especially important to ensure that cells & batteries are packed in such a way to prevent short circuits.

** The commodity is met the UN manual of Tests and Criteria, Part III, Sub-section 38.3 **Non-dangerous goods.

Such battery have been packed in inner packaging in such a manner as to effectively prevent short circuit and movement that could lead to short circuit.

Section 15 – Regulatory Information

Special requirement be according to the local regulatory.

Section 16 – Other Information

The data in this Material Safety Data Sheet relates only to the specific material designated herein.

Section 17 – Measures for fire extinction

In case of fire, it is permissible to use any class of extinguishing medium on these batteries or their packing material. Cool exterior of batteries if exposed to fire to prevent rupture.

Fire fighters should wear self-contained breathing apparatus.

GP Batteries

Material Safety Data Sheet for GP Lithium battery (Lithium Metal Battery)

Document Number: MCRA003W

Revision:19

Page 5 of 5

WEIGHT OF LITHIUM FOR LITHIUM BATTERY

Battery type	Model	Weight of cell (g)	Aggregated lithium equivalent content (g)
Cell	GPCR123A	16	0.56
	GPCR2	10	0.27
	GPCR1/3N	2.3	0.06
	GPCR14250	9	0.27
	GP15LF	14.5	0.96
Battery	GPCR-P2	37	1.12
	GP2CR5	37	1.12
	GPCR-V9	34	0.81