



Automotive 60 V, 5 A power Schottky rectifier



Features

- AEC-Q101 qualified 
- Avalanche capability specified
- 175 °C maximum junction temperature
- V_{RRM} guaranteed from -40 °C to 175 °C
- Wettable flanks for automatic visual inspection
- PPAP capable
- ECOPACK^{®2} compliant component

Application

- DC/DC converters
- Reverse polarity protection
- Freewheeling diodes
- Switching diodes

Description

The **STPS560SFY** power Schottky rectifier has been designed for automotive applications.

Packaged in PSMC (TO-277A), this device provides a very low V_F in a compact package which can withstand high operating junction temperature.

| Product status link | |
|----------------------------|--------|
| STPS560SFY | |
| Product summary | |
| Symbol | Value |
| $I_{F(AV)}$ | 5 A |
| V_{RRM} | 60 V |
| T_j (max.) | 175 °C |
| V_F (typ.) | 0.43 V |

1 Characteristics

Table 1. Absolute ratings (limiting values at 25 °C, unless otherwise specified with 2 anode terminals short-circuited)

| Symbol | Parameter | Value | Unit | |
|--------------------|--|---|------|---|
| V _{RRM} | Repetitive peak reverse voltage (T _j = -40 °C to +175 °C) | 60 | V | |
| I _{F(AV)} | Average forward current, δ = 0.5 square pulse | T _c = 160 °C | 5 | A |
| I _{FSM} | Surge non repetitive forward current | t _p = 10 ms sinusoidal | 230 | A |
| P _{ARM} | Repetitive peak avalanche power | t _p = 10 μs, T _j = 125 °C | 258 | W |
| T _{stg} | Storage temperature range | -65 to +175 | °C | |
| T _j | Operating junction temperature range ⁽¹⁾ | -40 to +175 | °C | |

1. $(dP_{tot}/dT_j) < (1/R_{th(j-a)})$ condition to avoid thermal runaway for a diode on its own heatsink.

Table 2. Thermal resistance parameters

| Symbol | Parameter | Typ. | Unit |
|----------------------|------------------|------|------|
| R _{th(j-c)} | Junction to case | 2.0 | °C/W |

For more information, please refer to the following application note:

- AN5088: Rectifiers thermal management, handling and mounting recommendations

Table 3. Static electrical characteristics (anode terminals short-circuited)

| Symbol | Parameter | Test conditions | Min. | Typ. | Max. | Unit | |
|-------------------------------|-------------------------|-------------------------|-----------------------------------|------|------|------|----|
| I _R ⁽¹⁾ | Reverse leakage current | T _j = 25 °C | V _R = V _{RRM} | - | | 50 | μA |
| | | T _j = 125 °C | | - | 8 | 25 | mA |
| V _F ⁽²⁾ | Forward voltage drop | T _j = 25 °C | I _F = 2.5 A | - | | 0.51 | V |
| | | T _j = 125 °C | | - | 0.36 | 0.41 | |
| | | T _j = 25 °C | I _F = 5 A | - | | 0.56 | |
| | | T _j = 125 °C | | - | 0.43 | 0.49 | |

1. Pulse test: t_p = 5 ms, δ < 2%

2. Pulse test: t_p = 380 μs, δ < 2%

To evaluate the conduction losses, use the following equation:

$$P = 0.33 \times I_{F(AV)} + 0.032 \times I_{F(RMS)}^2$$

For more information, please refer to the following application notes related to the power losses:

- AN604: Calculation of conduction losses in a power rectifier
- AN4021: Calculation of reverse losses in a power diode

1.1 Characteristics (curves)

Figure 1. Average forward current versus case temperature ($\delta = 0.5$)




Figure 2. Relative variation of thermal impedance junction to case versus pulse duration




Figure 3. Reverse leakage current versus reverse voltage applied (typical values)




Figure 4. Junction capacitance versus reverse voltage applied (typical values)




Figure 5. Forward voltage drop versus forward current (typical values)




Figure 6. Normalized avalanche power derating versus pulse duration ($T_j = 125^\circ\text{C}$)





Figure 7. Thermal resistance junction to ambient versus copper surface under tab (typical values, epoxy printed board FR4, $e_{\text{Cu}} = 35\ \mu\text{m}$) (PSMC (TO-277A))



2 Package information

In order to meet environmental requirements, ST offers these devices in different grades of ECOPACK® packages, depending on their level of environmental compliance. ECOPACK® specifications, grade definitions and product status are available at: www.st.com. ECOPACK® is an ST trademark.

2.1 PSMC (TO-277A) package information

- Epoxy meets UL94,V0
- Cooling method : by conduction (C)

Figure 8. PSMC (TO-277A) package outline




Table 4. PSMC (TO-277A) package mechanical data

| Ref. | Dimensions | | | | | |
|------|-------------|------|------|-----------------------------|-------|-------|
| | Millimeters | | | Inches (for reference only) | | |
| | Min. | Typ. | Max. | Min. | Typ. | Max. |
| A | 1.00 | 1.10 | 1.20 | 0.039 | 0.043 | 0.047 |
| b | 1.05 | 1.20 | 1.35 | 0.041 | 0.047 | 0.053 |
| b2 | 1.90 | 2.05 | 2.20 | 0.075 | 0.081 | 0.087 |
| b4 | | 0.75 | | | 0.029 | |
| C | 0.15 | 0.23 | 0.40 | 0.006 | 0.009 | 0.016 |
| D | 4.45 | 4.60 | 4.75 | 0.175 | 0.181 | 0.187 |
| D1 | 4.25 | 4.40 | 4.45 | 0.167 | 0.173 | 0.175 |
| D2 | 3.40 | 3.60 | 3.70 | 0.134 | 0.142 | 0.146 |
| E | 6.35 | 6.50 | 6.65 | 0.250 | 0.256 | 0.262 |
| E1 | 6.05 | 6.10 | 6.15 | 0.238 | 0.240 | 0.242 |
| E2 | 4.50 | 4.60 | 4.70 | 0.177 | 0.181 | 0.185 |
| E3 | | 3.94 | | | 1.55 | |
| e | | 2.13 | | | 0.084 | |
| e1 | | 3.33 | | | 0.131 | |
| G | | 1.20 | | | 0.047 | |
| G1 | | 0.70 | | | 0.027 | |
| L | 0.90 | 1.05 | 1.24 | 0.035 | 0.041 | 0.049 |
| L4 | 0.02 | | | 0.0008 | | |
| L5 | 0.02 | | | 0.0008 | | |

Figure 9. PSMC (TO-277A) package footprint in mm (in inches)





Figure 10. PSMC (TO-277A) marking



Figure 11. Package orientation in reel



Taped according to EIA-481
Note: Pocket dimensions are not on scale
Pocket shape may vary depending on package
Cathode band only on unidirectional devices

Figure 12. Tape and reel orientation




Figure 13. 13" reel dimension values




Figure 14. Inner box dimension values





Figure 15. Tape outline



Note: Pocket dimensions are not on scale
Pocket shape may vary depending on package

Table 5. Tape dimension values

| Ref. | Dimensions | | |
|------|-------------|------|------|
| | Millimeters | | |
| | Min. | Typ. | Max. |
| D0 | 1.5 | 1.55 | 1.6 |
| D1 | 1.5 | | |
| F | 5.45 | 5.5 | 5.55 |
| K0 | 1.3 | 1.4 | 1.5 |
| P0 | 3.9 | 4.0 | 4.1 |
| P1 | 7.9 | 8.0 | 8.1 |
| P2 | 1.95 | 2.0 | 2.05 |
| W | 11.7 | 12 | 12.3 |

3 Ordering information

Table 6. Ordering information

| Order code | Marking | Package | Weight | Base qty. | Delivery mode |
|------------|---------|----------------|--------|-----------|---------------|
| STPS560SFY | PS560Y | PSMC (TO-277A) | 90 mg | 6000 | Tape and Reel |

Revision history

Table 7. Document revision history

| Date | Version | Changes |
|-------------|---------|------------------|
| 22-Feb-2019 | 1 | Initial release. |

IMPORTANT NOTICE – PLEASE READ CAREFULLY

STMicroelectronics NV and its subsidiaries (“ST”) reserve the right to make changes, corrections, enhancements, modifications, and improvements to ST products and/or to this document at any time without notice. Purchasers should obtain the latest relevant information on ST products before placing orders. ST products are sold pursuant to ST’s terms and conditions of sale in place at the time of order acknowledgement.

Purchasers are solely responsible for the choice, selection, and use of ST products and ST assumes no liability for application assistance or the design of Purchasers’ products.

No license, express or implied, to any intellectual property right is granted by ST herein.

Resale of ST products with provisions different from the information set forth herein shall void any warranty granted by ST for such product.

ST and the ST logo are trademarks of ST. All other product or service names are the property of their respective owners.

Information in this document supersedes and replaces information previously supplied in any prior versions of this document.

© 2019 STMicroelectronics – All rights reserved