

## Product Overview

### NCS210R: Current Sense Amplifier, 26V, Low-/High-Side Voltage Out, Bidirectional Current Shunt Monitor

For complete documentation, see the data sheet.



The NCS210R and NCV210R (AEC-Q100 qualified) are voltage output current sense amplifiers that can measure voltage across shunts at common-mode voltages from -0.3 V to 26 V, independent of supply voltage. With a fixed gain of 200 V/V, the low offset of the zero-drift architecture enables current sensing with maximum drops across the shunt as low as 10 mV full-scale. These devices can operate from a single +2.2 V to +26 V power supply, drawing a maximum of 80  $\mu$ A of supply current. Available in UQFN and SC70 packages

Additional gain options are available:

NCS213R (50 V/V), NCS214R (100 V/V), NCS211R (500 V/V)

#### Similar Products:

	<a href="#">NCS210R</a>	<a href="#">NCS211R</a>	<a href="#">NCS213R</a>	<a href="#">NCS214R</a>
Gain (V/V)	200	500	50	100
Gain Error (%)	1	1	1	1
Offset Voltage ( $\mu$ V)	35	35	100	60

#### Features

- Wide common mode input range -0.3 to 26 V
- Low Offset Voltage:  $\pm 35$   $\mu$ V max.
- Low Offset Drift: 0.5  $\mu$ V/ $^{\circ}$ C max.
- Supply Voltage: 2.2 to 26V

#### Applications

- Power Monitoring
- Power Adapters
- LED Power Supply
- Over Current Protection
- Automotive

#### Benefits

- High- side current sensing for high voltage systems
- Low Ohm value current sense resistors
- High accuracy over temperature leading to better power efficiency
- Wide supply voltage range provides system flexibility

#### End Products

- White Goods
- Automotive
- Lighting
- Laptop/Notebooks PC
- Fast Chargers in Smartphones and Tablets

### Part Electrical Specifications

Product	Pricing (\$/Unit)	Compliance	Status	Channels	Gain (V/V)	Gain Error Max (%)	V <sub>s</sub> Min (V)	V <sub>s</sub> Max (V)	V <sub>CM</sub> (V)	I <sub>q</sub> Typ (mA)	Bandwidth Typ (-3dB)	V <sub>os</sub> Max (mV)	V <sub>os</sub> Drift Max ( $\mu$ V/ $^{\circ}$ C)	Operating Temperature Range ( $^{\circ}$ C)	CMR R Typ (dB)	Package Type
NCS210RMUTAG	0.2467	Pb-free Halide free non AEC-Q and PPAP	Active	1	200	$\pm 1$	2.2	26	-0.3 to 26	0.04	0.04	$\pm 0.035$	0.5	-40 to 125	125	UQFN-10
NCS210RSQT2G	0.2467	Pb-free Halide free non AEC-Q and PPAP	Active	1	200	$\pm 1$	2.2	26	-0.3 to 26	0.04	0.04	$\pm 0.035$	0.5	-40 to 125	125	SC-88-6 / SC-70-6 / SOT-363-6
NCV210RSQT2G	0.3067	AEC Qualified PPAP Capable Pb-free Halide free	Active	1	200	$\pm 1.5$	2.2	26	-0.3 to 26	0.04	0.04	$\pm 0.05$	1.5	-40 to 125	135	SC-88-6 / SC-70-6 / SOT-363-6

For more information please contact your local sales support at [www.onsemi.com](http://www.onsemi.com).

Created on: 10/16/2020