

MINITEK® ACTIVE LATCH HOUSING

OVERVIEW

Minittek® is FCI's brand for board to board and cable / wire to board connectors in 2.00mm (0.079in.) pitch. It is a fully modular system enabling all types of connections between PCBs, wires and flat cables. Its 2mm spacing allows up to 38% space saving compared to traditional modular systems.

FCI is the leading supplier of this type of modular system and continues to grow and expand it. We are now adding a new active latch housing and POKA YOKE feature to active latch for housing for wire-to-board applications

The latch ensures a secure mechanical connection in applications with high extraction forces or vibration. Unlike other systems on the market, the active latch housing mates with the standard headers from the Minittek® system. This ensures full modularity and interchangeability throughout the system.

The active latch housing is made with high temperature black plastic material which is able to withstand temperature up to 125°C. It is available in 15 versions from 2 x 3 to 2 x 17 positions.



FEATURES & BENEFITS

- The POKA YOKE feature offered by new shape of header ensures right mating. No pre-opening needed for mating.

TARGET MARKETS / APPLICATIONS

- Active latch type 2 now offers secure connection and POKA YOKE feature




APPLICATION




Crimp the terminal onto the wire.




Insert the terminals into the active latch housing.



Mate the active latch housing with the headers. It locks with a click without pre opening action needed.



Unmating can be effected by pressing the latch and removing the housing from the header.



Guiding bracket



TECHNICAL INFORMATION

MATERIALS

- Housing: Polyamide
- Colour: Black
- Flammability rating: UL94V-0

ELECTRICAL PERFORMANCE

- Insulation resistance: 1000MΩ min.
- Dielectric withstanding voltage: 500V



ENVIRONMENTAL

- Operating temperature range: -55°C to +125°C


MECHANICAL PERFORMANCE

- Latching retention force 15 N min. (for 2x3 & 2x4)
- Latching retention force 25 N min. (for 2x5 & 2x25)
- This product is RoHS compliant according to the European Union Directive 2002/95/IEC

SPECIFICATIONS

-  File no. E66906
-  File no. LR46923
- Product drawing: By 8-digit base part number
- Product specification: GS-12-415

PART NUMBERS



Description	Part Numbers
Shrouded headers	98414
Shrouded headers	98424
Shrouded headers	10075025
Crimp to wire contacts	77138
Crimp to wire contacts	10044403