



Features

- 3 kA, 8/20 µs surge capability
- Low clamping voltage under surge
- Bidirectional TVS
- Excellent performance over temperature

Applications


- AC line protection
- High power DC bus protection

PTVS3-xxxC-TH Series High Voltage, High Current TVS Diodes

General Information

The Model PTVS3-xxxC-TH high voltage, bidirectional TVS diode series is designed for use in AC line and high power DC bus clamping applications.

The devices are RoHS* compliant. They also meet IEC 61000-4-5 8/20 µs current surge requirements.



Absolute Maximum Ratings (@ T_A = 25 °C Unless Otherwise Noted)

Rating		Symbol	Value	Unit
Repetitive Standoff Voltage	PTVS3-380C-TH PTVS3-430C-TH	V _{WM}	380 430	V
Peak Current Rating per 8/20 µs IEC 61000-4-5		I _{PPM}	3	kA
Operating Junction Temperature Range		T _J	-55 to +125	°C
Storage Temperature Range		T _S	-55 to +150	°C
Lead Temperature, Soldering (10 s)			260	°C

Electrical Characteristics (@ T_A = 25 °C Unless Otherwise Noted)

Parameter	Test Conditions		Min.	Typ.	Max.	Unit
I _D Standby Current	V _D = V _{WM}				10	µA
V _(BR) Breakdown Voltage	I _{BR} = 10 mA	PTVS3-380C-TH PTVS3-430C-TH	401 440	422 465	443 490	V
V _C Clamping Voltage (1)	I _{PP} = 3 kA	PTVS3-380C-TH PTVS3-430C-TH		520 580		V
V _(BR) Temperature Coefficient				0.1		%/°C
C Capacitance	F = 10 kHz, V _d = 1 Vrms	PTVS3-380C-TH PTVS3-430C-TH		0.35 0.40		nF

(1) V_C measured at the time which is coincident with the peak surge current.

BOURNS®

Asia-Pacific: Tel: +886-2 2562-4117 • Fax: +886-2 2562-4116

EMEA: Tel: +36 88 520 390 • Fax: +36 88 520 211

The Americas: Tel: +1-951 781-5500 • Fax: +1-951 781-5700

www.bourns.com

*RoHS Directive 2002/95/EC Jan. 27, 2003 including annex and RoHS Recast 2011/65/EU June 8, 2011.

Specifications are subject to change without notice.

The device characteristics and parameters in this data sheet can and do vary in different applications and actual device performance may vary over time.


Users should verify actual device performance in their specific applications.

PTVS3-xxxC-TH Series High Voltage, High Current TVS Diodes


BOURNS®

Performance Graphs


V-I Characteristic




Typical V_{BR} vs. Junction Temperature



Typical Surge Current Derating



Current 8/20 μs Waveform per IEC 61000-4-5




This graph shows the typical device surge current derating versus ambient temperature when subjected to the 8/20 μs current waveform per the IEC 61000-4-5 specification.

This device is not intended for continuous operation at temperatures above 125 $^\circ\text{C}$.

Specifications are subject to change without notice.

The device characteristics and parameters in this data sheet can and do vary in different applications and actual device performance may vary over time. Users should verify actual device performance in their specific applications.

Typical Waveform Under Surge




PTVS3-xxxC-TH Series High Voltage, High Current TVS Diodes

BOURNS®

Product Dimensions

Epoxy encapsulation materials conform to UL 94V-0. Silver plated lead finish conforms to the solderability requirements of JESD22-B102, Pb free solder. Package dimensions are shown below:



Dim.	PTVS3-380C-TH	PTVS3-430C-TH
A	24.15 ± 0.72 (0.951 ± 0.028)	
B	2.40 ± 0.50 (0.094 ± 0.020)	
C	1.75 ± 1.25 (0.069 ± 0.049)	
D	10.80 Max. (0.425)	
E	1.25 ± 0.05 (0.049 ± 0.002)	
F	9.30 Max. (0.366)	
G	16.50 Max. (0.650)	
H	6.00 ± 1.00 (0.236 ± 0.039)	

Typical Part Marking

PTVS3-380C-TH 3380
PTVS3-430C-TH 3430

How to Order

PTVS 3 - 380 C - T H

Series _____
PTVS = Power TVS High Current Diode

Peak Current Rating _____
3 = 3 kA

Repetitive Standoff Voltage _____
380 = 380 V
430 = 430 V

Suffix _____
C = Bidirectional Device

Package _____
T = Through-Hole

Temperature _____
H = High Temperature Series